




CLIFE-2PRO-SMS-HVG-600

Bare Emergency Batten 600mm, Twin Lifelight Pro, Surface Mount, LP,
Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION

Part Number	CLIFE-2PRO-SMS-HVG-600
MIC	AUT02910060001
Description	Bare Emergency Batten 600mm, Twin Lifelight Pro, Surface Mount, LP, Zoneworks XT Hive 2.4GHz
Construction	Powder coated metal enclosure
Mounting	Surface Mount, can also be chain suspended
Dimensions L x W x H	610mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 6.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D160 C90=D160
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt. (QTY 2)
8003081	LED:PCA: LLPRO HEAD Alum #CT10640-D4 - GW CSHPM 'LT' (QTY 2)
CLIFE-PRO-CKIT-HVGEXTA-NP	Lifelight Pro, Control Only, HVGEXTA, LP (QTY 2) (incl. HV node)
8003580	PCA: V5 2.4GHz RF Node CT10816-A1 Ext Ant (QTY 2)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.