




CLIFE-D2-BLK

Lifelight Emergency, Recessed Mount, LP,
DALI Emergency, Black



PRODUCT INFORMATION

Part Number	CLIFE-D2-BLK
MIC	AUT00000001001
Description	Lifelight Emergency, Recessed Mount, LP, DALI Emergency, Black
Construction	PC/ABS head
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack), 95mm Head Diameter (145mm with adaptor plate)
Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
Inrush Current (Peak/Duration)	12.093mA / 37µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	Battery
AUM02270590001 CLIFE-CKIT-D2	Driver Pack
1100924	LED Head Assembly
8003062	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order