



CLIFE-D2

Lifelight Emergency, Recessed Mount, CLP, DALI-2
Emergency



PRODUCT INFORMATION	
Part Number	CLIFE-D2
MIC	UKT00000019401
Description	Lifelight Emergency, Recessed Mount, CLP, DALI-2 Emergency
Material	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate (LiFePO4), 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.026A
Power Factor	0.7
Total Lumen Output	200lm (Emergency)
Power Consumption	1.4 Watts (Standby), 4.7 Watts (Max)
Inrush Current (Peak/Duration)	TBC
Earth Leakage	TBC
IP Rating	IP20
Operating Temperature	0°C to 40°C
Maximum Case Temperature (TC)	70°C
Rated Emergency Duration	180 minutes
Compliance Marking	
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598-2-22, BS 5266



CLIFE-D2

Lifelight Emergency, Recessed Mount, CLP, DALI-2
Emergency

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550092	Battery
UKM02270030002	Emergency Driver
1100932	Emergency LED Panel
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order