

## CLEVERTRONICS LP LIFELIGHT (ZONENWORKS XT HIVE)



### PRODUCT INFORMATION

Part Number	CLIFE-HV-BLK
MIC	AUD02810050002
Description	LP Premium Lifelight, high performance, recessed Emergency Light, Black
Construction	ABS head and PC/ABS control gear
Mounting	Recessed mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
AUM02870080001 CLIFE-CKIT-HV	Lifelight, Control Only, HV, LP, OWC, 650mA (incl HV Node)
1100924	LIFELight Head Assembl, Round, LT, 1LED, Blk
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order