

CLIFE-HVG

Lifelight Emergency, Recessed Mount, CLP, Zoneworks XT Hive



| PRODUCT INFORMATION | | | | |
|--------------------------------|--|--|--|--|
| Part Number | CLIFE-HVG | | | |
| MIC | UKD02810060002 | | | |
| Description | Lifelight Emergency, Recessed Mount, CLP, Zoneworks XT Hive | | | |
| Construction | PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear | | | |
| Mounting | Recessed Mount | | | |
| Dimensions L x W x H | 232mm x 51mm x 42mm (Control Pack), 95mm Head Diameter (145mm with adaptor plate) | | | |
| Ceiling Hole Cut-Out | 85mm, 135mm (with adaptor plate) | | | |
| Minimum Ceiling Depth | 120mm, 70mm (with adaptor plate) | | | |
| Weight | 0.8kg | | | |
| Operating Mode | Non-maintained | | | |
| Testing System | Zoneworks XT HIVE (RF) | | | |
| Battery Type & Manufacturer | Lithium Iron Phosphate (LiFePO4), Clevertronics | | | |
| Charging Method | Intelligent current limited constant voltage | | | |
| Lamp(s) | 1 x LED | | | |
| Operating Voltage | 220-240V AC; 50Hz | | | |
| Power Consumption | 1.4 Watts (Standby), 4.7 Watts (Max) | | | |
| Inrush Current (Peak/Duration) | 0.3A/3668µs | | | |
| Earth Leakage | N/A | | | |
| Total lumen output | 200lm (Emergency) | | | |

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.





CLIFE-HVG

Lifelight Emergency, Recessed Mount, CLP, Zoneworks XT Hive

| PRODUCT INFORMATION | | | | | | |
|--------------------------|---|---|-----|-----|--|--|
| Rated Emergency Duration | 180 minutes | | | | | |
| IP Rating | IP20 | | | | | |
| Operating temperature | 0°C to 40°C | | | | | |
| Protection | Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts | | | | | |
| Luminaire Classification | X | 0 | ADF | 180 | | |
| Applicable Standards | BS EN 60598-2-22, BS 5266 | | | | | |
| Compliance Marking | UK (€ | | | | | |

| REPLACEMENT PARTS | | |
|--------------------------------------|---------------|--|
| PART NUMBER | DESCRIPTION | |
| 1553092 | Battery | |
| 1100923 | Emergency LED | |
| UKM02870020002 CLIFE-CKIT-HVG-500 | Driver Pack | |
| 8003330 | Hive Node | |

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

