



CLIFE-PRO-D2-BLK-F5C

Lifelight Pro Emergency, Recessed Mount, LP, DALI-2 Emergency, Black, Fitted with Customer Supplied 5-Core Lead



PRODUCT INFORMATION

Part Number	CLIFE-PRO-D2-BLK-F5C
MIC	AUT00000004901
Description	Lifelight Pro Emergency, Recessed Mount, LP, DALI-2 Emergency, Black, Fitted with Customer Supplied 5-Core Lead
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm head diameter (98mm with adaptor plate)
Cut-Out	51mm (85mm with adaptor plate)
Minimum Depth	200mm (120mm with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush Current	13.313A @ 66µs
Earth Leakage	0.326mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
AUM02270560001 CLIFE-PRO-CKIT-D2	Driver
1100871	LED Head Assembly
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order