



CLIFE-PRO-D2-RECWP-WHT

Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, LP, DALI-2
Emergency



White LED Head and Front Ring

PRODUCT INFORMATION	
Part Number	CLIFE-PRO-D2-RECWP-WHT
MIC	AUT00000020201
Description	Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, LP, DALI-2 Emergency
Construction	Die Cast Aluminium Body, 316 Stainless Steel Screws, Clear Toughened Glass
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm head diameter
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V~50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Supply Current	0.034A
Power Factor	0.387
Inrush Current (Peak/Duration)	13.313A/66µs
Earth Leakage	0.344mA
IP Rating	IP65 (Lamp head only)
IK Rating	IK10
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550230	Battery
AUM02270680001	Emergency Driver
1100819	LED Head
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.