



CLIFE-PRO-D2

Lifelight Pro Emergency, Recessed Mount, CLP, DALI-2 Emergency



PRODUCT INFORMATION

Part Number	CLIFE-PRO-D2			
MIC	UKT00000012801			
Description	Lifelight Pro Emergency, Recessed Mount, CLP, DALI-2 Emergency			
Construction	PC/ABS Head. Double/reinforced insulation between supply and battery circuit of lamp control gear			
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)			
Ceiling Hole Cut-Out	51mm (85mm with adaptor plate)			
Minimum Ceiling Depth	200mm (120mm with adaptor plate)			
Operating Mode	Non-maintained			
Testing System	DALI-2			
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent current limited constant voltage			
Lamp(s)	2 x LED			
Operating Voltage	220-240V AC; 50Hz			
Supply Current	TBC			
Power Factor	TBC			
Power Consumption	0.3 Watts (Standby), 3.0 Watts (Max)			
Total lumen output	398lm (Emergency)			
Inrush Current (Peak/Duration)	13.313A @ 66µs			
Earth Leakage	0.326mA			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Luminaire Classification	X	0	ADF	180
Applicable Standards	BS EN 60598-2-22, BS 5266			
Compliance Marking	UK CA CE			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550229	Battery
1100897	LED Panel
UKM02270070002	Emergency Driver
8003062	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.