



CLIFE-PRO-DALI-BLK

CLEVERTRONICS CLP LIFELIGHT PRO, BLACK



PRODUCT INFORMATION

Part Number	CLIFE-PRO-DALI-BLK
MIC	UKT02210060002
Description	CLP Premium LifeLight PRO, High Performance, Recessed Emergency Light, Black
Construction	PC/ABS Head. Double/reinforced insulation between supply and battery circuit of lamp control gear
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm (85mm with adaptor plate)
Minimum Ceiling Depth	200mm (120mm with adaptor plate)
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.3 Watts (Standby), 3.0 Watts (Max)
Total lumen output	398lm (Emergency)



*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



CLIFE-PRO-DALI-BLK

CLEVERTRONICS CLP LIFELIGHT PRO, BLACK

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts			
Luminaire Classification	X	0	ADF	180
Applicable Standards	BS EN 60598-2-22, BS 5266			
Compliance Marking	 			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550229	BATT:LP 3.2V 6400mAh 200mm lead, Sleeve
1100894	UK,LifelightPro HeadAssbly,Rnd,Lrge+Rg,Gen2,LT,Blk
UKM02270070002 CLIFE-PRO-CKIT-DALI-475	Lifelight Pro, Control Only, Dali Reg, CLP, 475mA
8003060	PCA: New DALI #CT10629-Ax

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.