

CLIFE-PRO-DALICLEVERTRONICS CLP LIFELIGHT PRO



PRODUCT INFORMATION			
Part Number	CLIFE-PRO-DALI		
MIC	UKT02210010002		
Description	CLP Premium LifeLight PRO, High Performance, Recessed Emergency Light		
Construction	PC/ABS Head. Double/reinforced insulation between supply and battery circuit of lamp control gear		
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)		
Ceiling Hole Cut-Out	51mm (85mm with adaptor plate)		
Minimum Ceiling Depth	200mm (120mm with adaptor plate)		
Operating Mode	Non-maintained		
Testing System	DALI Registered		
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics		
Charging Method	Intelligent current limited constant voltage		
Lamp(s)	2 x LED		
Operating Voltage	220-240V AC; 50Hz		
Power Consumption	0.3 Watts (Standby), 3.0 Watts (Max)		
Total lumen output	398lm (Emergency)		

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.





CLIFE-PRO-DALI CLEVERTRONICS CLP LIFELIGHT PRO

PRODUCT INFORMATION						
Rated Emergency Duration	180 minutes					
IP Rating	IP20					
Operating temperature	0°C to 40°C					
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts 					
Luminaire Classification	Х	0	ADF	180		
Applicable Standards	BS EN 60598-2-22, BS 5266					
Compliance Marking	UK C€					

REPLACEMENT PARTS			
PART NUMBER	DESCRIPTION		
1550229	BATT:LP 3.2V 6400mAh 200mm lead, Sleeve		
1100897	UK,Lifelight Pro Head Assbly,Rnd,LargeRing,Gen2,LT		
UKM02270070002 CLIFE-PRO-CKIT-DALI-475	Lifelight Pro, Control Only, Dali Reg, CLP, 475mA		
8003060	PCA: New DALI #CT10629-Ax		

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

