



CLIFE-PRO-HVG-BLK

Clevertronics LP Led Emergency Luminaire



PRODUCT INFORMATION

Part Number	CLIFE-PRO-HVG-BLK				
MIC	UKT02810070001				
Description	CLP Premium LifeLight PRO, Recessed Emergency Light with Zoneworks Hive 2.4GHz, Black				
Construction	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear				
Mounting	Recessed Mount				
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)				
Cut-Out	51mm, 85mm (with adaptor plate)				
Minimum Depth	200mm, 120mm (with adaptor plate)				
Weight	0.6kg				
Operating Mode	Non-Maintained				
Testing System	Zoneworks XT HIVE (RF) 2.4GHz				
Battery	Lithium Iron Phosphate, 3.2V 6400mAh				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	0.7W (Standby), 3.0W (Max)				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating Temperature	0°C to 40°C (LifeLight Head) 0°C to 60°C (Driver)				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts				
Luminaire Classification	X	0	ADF	180	
Conformity	BS EN 60598.2.22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550229	Battery
1100894	LED Head Assembly
UKM02870030001	Driver Pack
8003330	Communications Node – HVG

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.