




CLIFE-PRO-HVG-RECWP-BLK

Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, LP, Zoneworks XT Hive, Black



PRODUCT INFORMATION

Part Number	CLIFE-PRO-HVG-RECWP-BLK
MIC	AUT02920100001
Description	Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, LP, Zoneworks XT Hive, Black
Construction	Die Cast Aluminium Body, 316 Stainless Steel Screws, Clear Toughened Glass
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm diameter (Lamp head)
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF), 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max during 16-hour charge)
IP Rating	IP65 (Lamp head only)
IK Rating	IK10 (Lamp head only)
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D50 C ₉₀ =D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
1100817	LED Assembly
AUM02970050002	Emergency Driver
8003560	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order