

Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, LP Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-HVG-RECWP-WHT
MIC	AUT02920020001
Description	Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, LP, Zoneworks XT Hive 2.4GHz
Construction	Die Cast Aluminium Body 316 Stainless Steel Screws Clear Toughened Glass
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm (head diameter)
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP65 (Lamp head only)
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Impact Rating	IK10

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT-HVG	Lifelight Pro, Control Only, LP, HVG (incl. Hive node)
1100843	Lifelight Pro Head Assembly, Round, Blk, Gen 2
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order