



CLIFE-PRO-HVG

Lifelight Pro Emergency, Recessed Mount, LP, Zoneworks Hive



PRODUCT INFORMATION

Part Number	CLIFE-PRO-HVG
MIC	AUT02910010002
Description	Lifelight Pro Emergency, Recessed Mount, LP, Zoneworks Hive
Construction	ABS head, PC/ABS control gear
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm head diameter (98mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery Type & Manufacturer	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V~ 50Hz
Supply Current	0.05A
Power Factor	0.566
Power Consumption	0.5 Watts (Standby), 3.7 Watts (Max)
Inrush current (Peak/Duration)	18.5A / 142 μ s
Earth Leakage	0.346mA
IP Rating	IP20
Impact Rating	IK03
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80, C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	☐ Class II double insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
1100868	LED Head
AUM02970050003	Emergency Driver
8003572	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order