



## CLIFE-PRO-HVG

CLEVERTRONICS CLP LIFELIGHT PRO  
(ZONWORKS HIVE)



PRODUCT INFORMATION				
Part Number	CLIFE-PRO-HVG			
MIC	UKT02810060001			
Description	CLP Premium LifeLight PRO, High Performance, Recessed Emergency Light			
Construction	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear			
Mounting	Recessed Mount			
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)			
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)			
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)			
Weight	0.6kg			
Operating Mode	Non-maintained			
Testing System	Zoneworks XT HIVE (RF)			
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Lamp(s)	2 x LED			
Operating Voltage	220-240V AC; 50Hz			
Total Lumen Output	398lm (Emergency)			
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C (Lifelight Head) 0°C to 60°C (Driver)			
Protection	<ul style="list-style-type: none"> <li>Battery overvoltage &amp; overcurrent protection</li> <li>Battery deep discharge protection</li> <li>Supply voltage polarity reversal protection</li> <li>Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts</li> </ul>			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598.2.22, BS 5266			

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



**CLIFE-PRO-HVG**  
CLEVERTRONICS CLP LIFELIGHT PRO  
(ZONWORKS HIVE)

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550229	BATT:LP 3.2V 6400mAh 200mm lead, Sleeve
1100897	UK,Lifelight Pro Head Assbly,Rnd,LargeRing,Gen2,LT
UKM02870030001	CLIFE-PRO-CKIT-HVG-475, Lifelight Pro, Control Only, LP, HVG, 475mA
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice