




CLIFE-PRO-RECSP-D2-BLK

Lifelight Pro IP44 Splashproof Emergency, Recessed Mount, LP, DALI-2 Emergency, Black



PRODUCT INFORMATION

Part Number	CLIFE-PRO-RECSP-D2-BLK
MIC	AUT00000003301
Description	Lifelight Pro IP44 Splashproof Emergency, Recessed Mount, LP, DALI-2 Emergency, Black
Construction	PC/ABS head
Mounting	Recessed Ceiling Note: due to the small head/ceiling cut-out, the plug won't fit through the hole and access from behind/above the ceiling is required for installation
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm Head diameter
Ceiling Hole Cut-Out	51mm
Minimum Ceiling Depth	200mm
Operating Mode	Non-Maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Factor	TBA
Supply Current	TBA
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush Current (Peak/Duration)	TBA
Earth Leakage	TBA
IP Rating	IP44 (parts below ceiling) IP20 (parts above ceiling), see image below
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
8050260	LED Panel
AUM02270190003	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

IP Ratings:

