



CLIFE-PRO-SM-D2-BLK

LP LIFELIGHT PRO IP65 WEATHERPROOF
SURFACE MOUNT EMERGENCY, DALI-2



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | CLIFE-PRO-SM-D2-BLK |
| MIC | AUT02210460001 |
| Description | LP Premium Lifelight PRO, High Performance, Surface Mounted Emergency Light, Black, DALI-2 |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 247mm x 125mm x 48mm |
| Weight | 0.7kg |
| Operating Mode | Non-maintained |
| Testing System | DALI-2 |
| Battery | Lithium Iron Phosphate, 3.2V 6400mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Earth Leakage | 0A |
| Inrush Current | 12.093A/87.3uS |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 0.7W (Standby), 3.0W (Max) |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C0=D80 C90=D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1550231 | Battery |
| 8050170 | LED Strip |
| 8003501 | Driver |
| 8003062 | DALI-2 Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.