



## CLIFE-PRO-SM-HVG-BLK

Lifelight Pro Emergency, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, Black



### PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SM-HVG-BLK
MIC	AUT02910050001
Description	Lifelight Pro Emergency, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby) 3.0W (Max)
Inrush Current (Peak/ Duration)	13.313A/66µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80, C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	<input type="checkbox"/> Class II double insulated

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	Battery
8003081	LED Panel
8003501	Emergency Driver
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.