



CLIFE-PRO-SM-HVG

Lifelight Pro Emergency, Surface Mount, CLP, Zoneworks XT Hive



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SM-HVG			
MIC	UKT02810010002			
Description	Lifelight Pro Emergency, Surface Mount, CLP, Zoneworks Hive			
Construction	Polycarbonate Enclosure			
Mounting	Surface Mount			
Dimensions L x W x H	242mm x 125mm x 48mm			
Weight	0.7kg			
Operating Mode	Non-Maintained			
Testing System	Zoneworks HIVE (RF) 2.4GHz			
Battery	Lithium Iron Phosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Lamp(s)	2 x LED			
Operating Voltage	220-240V~50Hz			
Supply Current	0.031A			
Power Factor	0.302			
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)			
Inrush Current (Peak/Duration)	14A/248µs			
Earth Leakage	N/A			
Total Lumen	350lm (Emergency)			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)			
Operating temperature	0°C to 40°C			
Compliance Marking				
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553231	Battery
8003081	LED Strip
8003823	Driver Pack
8003330	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.