



## CLIFE-PRO-SM-WL-BLK

LP Premium Lifelight Pro, Surface Mounted Emergency Light  
with Warehouse Lens, Clevertest Plus Enabled, Black



| PRODUCT INFORMATION             |   |
|---------------------------------|---|
| Part Number                     | CLIFE-PRO-SM-WL-BLK   |
| MIC                             | AUT02310340001  |
| Description                     | LP Premium Lifelight Pro, Surface Mounted Emergency Light with Warehouse Lens, Clevertest Plus Enabled, Black |
| Construction                    | Polycarbonate Enclosure   |
| Mounting                        | Surface Mounted   |
| Dimensions L x W x H            | 247mm x 129mm x 51mm  |
| Weight                          | 0.8kg   |
| Operating Mode                  | Non-maintained  |
| Testing System                  | Clevertest Plus Enabled   |
| Battery                         | Lithium Iron Phosphate, 3.2V 6400mAh  |
| Charging Method                 | Intelligent Current Limited Constant Voltage  |
| Lamp(s)                         | Dual LED (Lifetime warranty on the lamp head and loom assembly)   |
| Operating Voltage               | 220-240V~ 50Hz  |
| Power Consumption               | 0.4W (Standby) 2.7W (Max)   |
| Inrush Current (Peak/ Duration) | 13.313A/66µs  |
| Earth Leakage                   | N/A   |
| IP Rating                       | IP20  |
| IK Rating                       | IK08  |
| Operating Temperature           | 1°C to 40°C   |
| AS2293 Classification           | N/A – Refer to Manufacturers' Recommended Spacing Table on the next page                                      |
| Applicable Standards            | AS/NZS3820, CISPR15, AS/NZS2293.3   |
| Compliance Marking (RCM)        |   |
| Appliance Class                 | Class II Double Insulated   |

| REPLACEMENT PARTS |                |
|-------------------|----------------|
| PART NUMBER       | DESCRIPTION    |
| 1550231           | Battery        |
| 2750403           | Warehouse Lens |
| 8050880           | LED Strip      |
| 8003501           | Driver         |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.



## CLIFE-PRO-SM-WL-BLK

LP Premium Lifelight Pro, Surface Mounted Emergency Light with Warehouse Lens, Clevertest Plus Enabled, Black

### SPACING TABLE

Manufacturer recommended spacing table and mounting heights for  $\leq 3.6\text{m}$  aisle width, based on direct illuminance calculations (AS/NZS 2293.1); minimum light level of 0.2lx / 0.5lx avg

| Mounting Height [m]    | 6.0  | 7.0  | 8.0  | 9.0  | 10.0 | 11.0 | 12.0 | 13.0 | 14.0 |
|------------------------|------|------|------|------|------|------|------|------|------|
| Fitting to Wall [m]    | 23.2 | 25.2 | 27.5 | 30.2 | 32.0 | 33.6 | 34.6 | 35.6 | 38.6 |
| Fitting to Fitting [m] | 55.0 | 61.1 | 66.8 | 72.1 | 74.2 | 58.6 | 45.0 | 33.5 | 18.3 |

Note: These spacing tables are a guide to assist with placement of the emergency luminaire and any design must be verified via illuminance calculations in accordance with AS/NZS2293.1:2018, section 4.6.1.3 *Illuminance calculations*

### ISOLUX PATTERN

