



CLIFE-PRO-SM-WP-D2-BLK

Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, CLP, DALI-2
Emergency, Black



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SM-WP-D2-BLK				
MIC	UKT00000018901				
Description	Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, CLP, DALI-2 Emergency, Black				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	247mm x 129mm x 51mm				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	DALI-2				
Battery Type & Manufacturer	Lithium Iron Phosphate, 3.2V 6400mAh				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	2 x LED				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	333lm (Emergency)				
Power Consumption	0.7W (Standby) 3.0W (Max)				
Inrush Current (Peak/Duration)	18.9A/138us				
Earth Leakage	N/A				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)				
Operating temperature	0°C to 40°C				
Luminaire Classification	X	0	ADF	180	
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553231	Battery
8050170	LED Panel
8003823	Emergency Driver
8003062	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice