



CLIFE-PRO-SM-WP-D2

Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, LP, DALI-2 Emergency



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SM-WP-D2
MIC	AUT02220190001
Description	Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, LP, DALI-2 Emergency
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Ceiling Cut-Out	N/A
Weight	0.8 kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
Inrush Current (Max)	13.3A/66uS
Earth Leakage	N/A
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	Battery
8050170	LED Strip
8003501	Driver
8003062	D2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing