



CLIFE-PRO-SM-WP-D2

Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, CLP, DALI-2 Emergency



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SM-WP-D2			
MIC	UKT02220060001			
Description	Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, CLP, DALI-2 Emergency			
Construction	Polycarbonate Enclosure			
Mounting	Surface Mounted			
Dimensions L x W x H	247mm x 129mm x 51mm			
Weight	0.8kg			
Operating Mode	Non-maintained			
Testing System	DALI-2			
Battery Type & Manufacturer	Lithium Iron Phosphate, 3.2V 6400mAh, Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Lamp(s)	2 x LED			
Operating Voltage	220-240V AC; 50Hz			
Total Lumen Output	333lm (Emergency) with Area Lens			
Power Consumption	0.7W (Standby) 3.0W (Max)			
Inrush Current (Peak/Duration)	18.9A/138uS			
Earth Leakage	N/A			
Rated Emergency Duration	180 minutes			
IP Rating	IP65			
IK Rating	IK08			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)			
Operating temperature	0°C to 40°C			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553231	Battery
8050170	LED Head
8003823	Driver
8003062	DALI-2 Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice