



CLIFE-PRO-SM-WP-DALI

Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, LP, DALI Emergency



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SM-WP-DALI
MIC	AUT02220060002
Description	Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, LP, DALI Emergency
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D80 C90=D80

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	Battery
8050170	LED Assembly
8003501	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order