

CLIFE-PRO-SM-WP-WL-D2

Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, LP, DALI-2 Emergency, Warehouse Lens



PRODUCT INFORMATION						
Part Number	CLIFE-PRO-SM-WP-WL-D2					
MIC	AUT00000016401					
Description	Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, LP, DALI-2 Emergency, Warehouse Lens					
Construction	Polycarbonate Enclosure					
Mounting	Surface Mounted					
Dimensions L x W x H	247mm x 129mm x 51mm					
Weight	0.8kg					
Operating Mode	Non-maintained					
Testing System	DALI-2					
Battery	Lithium Iron Phosphate, 3.2V 6400mAh					
Charging Method	Intelligent Current Limited Constant Voltage					
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly					
Operating Voltage	240V AC; 50Hz					
Power Factor	ТВА					
Supply Current	ТВА					
Power Consumption	0.7W (Standby), 3.0W (Max)					
Inrush Current (Peak/ Duration)	13.313A/66µs					
Earth Leakage	N/A					
IP Rating	IP65					
IK Rating	IK08					
Operating Temperature	0°C to 40°C					
AS2293 Classification	N/A –Refer to Manufacturers' Recommended Spacing Table on the next pag					
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3					
Compliance Marking (RCM)	<u>&</u>					
Appliance Class	Class II double insulated					

REPLACEMENT PARTS				
PART NUMBER	DESCRIPTION			
1550231	Battery			
8050880	LED Panel			
8003501	Emergency Driver			
8003062	Node			

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.





CLIFE-PRO-SM-WP-WL-D2

Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, LP, DALI-2 Emergency, Warehouse Lens

SPACING TABLE

Manufacturer recommended spacing table and mounting heights for ≤ 3.6m aisle width, based on direct illuminance calculations (AS/NZS 2293.1); minimum light level of 0.2lx / 0.5lx avg												
Mounting Height [m]	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0			
Fitting to Wall [m]	23.2	25.2	27.5	30.2	32.0	33.6	34.6	35.6	38.6			
Fitting to Fitting [m]	55.0	61.1	66.8	72.1	74.2	58.6	45.0	33.5	18.3			

Note: These spacing tables are a guide to assist with placement of the emergency luminaire and any design must be verified via illuminance calculations in accordance with AS/NZS2293.1:2018, section 4.6.1.3 *Illuminance calculations*



