



## CLIFE-PRO-SM-WP

Lifelight Pro IP65 Weatherproof Emergency,  
Surface Mount, CLP, Clevertest Plus



PRODUCT INFORMATION	
Part Number	CLIFE-PRO-SM-WP
MIC	UKT02320030002
Description	Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, CLP, Clevertest Plus
Material	Polycarbonate Enclosure
Mounting	Surface mount
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x White LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V AC; 50Hz
Supply Current	31mA (Standby), 46mA (Max)
Power Consumption	0.4W (Standby), 2.7W (Max)
Operating Temperature	0°C to 40°C
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Inrush Current (peak/duration)	14A / 248µs
Earth Leakage	N/A
Total Lumen Output	350lm (Emergency)
IP Rating	IP65
IK Rating	IK08
Emergency Duration	180 Minutes
Compliance Marking	
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li></ul>
Luminaire Classification	X   0   AD   180
Conformity	BS EN 60598-2-22, BS 5266



## CLIFE-PRO-SM-WP

Lifelight Pro IP65 Weatherproof Emergency,  
Surface Mount, CLP, Clevertest Plus

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553231	Battery
8050170	LED Assembly
8003823	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order