



## CLIFE-PRO-SMC-BLK

CLEVERTRONICS CLP LIFELIGHT PRO CYLINDER  
SURFACE MOUNT EMERGENCY - BLACK



### PRODUCT INFORMATION

Part Number	CLIFE-PRO-SMC-BLK
MIC	UKT02510120201
Description	CLP Premium Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light, Black, Clevertest Plus Enabled
Construction	Powder coated metal enclosure, PC/ABS head
Dimensions L x W x H	128mm Diameter, 245mm Height
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.4Watts (Standby), 2.7Watts (Max)
Total lumen output	380lm (Emergency)

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



## CLIFE-PRO-SMC-BLK

CLEVERTRONICS CLP LIFELIGHT PRO CYLINDER  
SURFACE MOUNT EMERGENCY - BLACK

### PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li><li>• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li></ul>				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table>	X	0	AD	180
X	0	AD	180		
Conformity	BS EN 60598-2-22, BS 5266				

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead. BRKT
1100809	UK,Lifelight Pro Head Ass,Ld:280mm,Rnd,Gen2,LT,Blk
UKM02370030002 CLIFE-PRO-SMS-CKIT-IC2-475	Lifelight Pro Control Only, 475mA, LP, CTP, OWC

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.