




CLIFE-PRO-SMS-D2-SPOT

Lifelight Pro Surface Mount Emergency Spotlight, DALI-2



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SMS-D2-SPOT
MIC	AUT02210470001
Description	Lifelight PRO, Surface Mount Emergency Spot Light, DALI-2
Construction	PC/ABS Head, Metal Enclosure. Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Surface mount
Dimensions L x W x H	267mm x 148mm x 60mm (base assembly) 105mm (lamp head and swivel assembly)
Weight	2.0kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
AUM02270540001 CLIFE-PRO-CKIT-D2-NP	Driver Pack
8003062	DALI-2 Node
8002130	LED Head Assembly

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.