



## CLIFE-PRO-SMS-SPOT-BLK

Lifelight Pro Single Spot Emergency, Surface Mount, LP, Clevertest Plus, Black



### PRODUCT INFORMATION

Part Number	CLIFE-PRO-SMS-SPOT-BLK
MIC	AUT02310360001
Description	Lifelight Pro Single Spot Emergency, Surface Mount, LP, Clevertest Plus, Black
Construction	PC/ABS Head, Metal Enclosure. Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Surface Mounted
Dimensions L x W x H	267mm x 148mm x 60mm (base assembly) 105mm (lamp head and swivel assembly)
Weight	2.0kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.3W (Standby), 2.6W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
1100817	LED Head Assembly
CLIFE-PRO-SMS-CKIT-NP AUM02370610001	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order