



CLIFE-PRO-SM

Lifelight Pro Emergency, Surface Mount, LP, Clevertest Plus



| PRODUCT INFORMATION | |
|---------------------------------|---|
| Part Number | CLIFE-PRO-SM |
| MIC | AUT02310110002 |
| Description | Lifelight Pro Emergency, Surface Mount, LP, Clevertest Plus |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Weight | 0.7kg |
| Operating Mode | Non-maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Iron Phosphate, 3.2V 6400mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 220-240V~ 50Hz |
| Power Factor | 0.566 |
| Supply Current | 0.028A |
| Power Consumption | 0.2W (Standby) 3.4W (Max) |
| Inrush Current (Peak/ Duration) | 18.5A/142µs |
| Earth Leakage | N/A |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0=D80, C90=D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |
| Appliance Class | <input type="checkbox"/> Class II double insulated |

| REPLACEMENT PARTS | |
|-------------------|------------------|
| PART NUMBER | DESCRIPTION |
| 1550231 | Battery |
| 8003081 | LED Panel |
| 8003403 | Emergency Driver |
| 8002912 | Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order