

CLEVERTRONICS CLP LIFELIGHT PRO SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SM		
MIC	UKT02310050001		
Description	CLP Premium LifeLight PRO, High Performance, Surface Mounted Emergency Light with Clevertest Plus Enabled		
Construction	Polycarbonate Enclosure		
Mounting	Surface Mounted		
Dimensions L x W x H	242mm x 125mm x 48mm		
Weight	0.7kg		
Operating Mode	Non-maintained		
Testing System	Clevertest Plus Enabled (Not activated by default)		
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO ₄), Clevertronics		
Charging Method	Intelligent Current Limited Constant Voltage		
Lamp(s)	2 x LED		
Operating Voltage	220-240V AC; 50Hz		
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)		
Rated Emergency Duration	180 minutes		
IP Rating	IP20		
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)		
Operating temperature	0°C to 40°C		
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts 		
Luminaire Classification	X	0	AD 180
Conformity	BS EN 60598.2.22, BS 5266		

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	BATT:LP 3.2V 6400mAh.200mm lead, No Brkt
8002912	PCA: CT10142-L9 2C250/475mA CTP UK

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.