



CLIFE-PRO-SPOT-BLK

Lifelight Pro Single Spot Emergency, Recessed Mount, LP, Clevertest Plus, Black



PRODUCT INFORMATION

Part Number	CLIFE-PRO-SPOT-BLK
MIC	AUT02310260001
Description	Lifelight Pro Single Spot Emergency, Recessed Mount, LP, Clevertest Plus, Black
Construction	PC/ABS Head, Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Lamp head assembly: Ceiling or wall mount with adjustable lamp head direction Control gear and battery: Remote mounted and connected via the standard 1m length of cable (same as the standard Lifelight PRO)
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 100mm x 60mm (Lamp Head and Swivel)
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby), 2.4W (Maintained Standby), 4.7W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=N/A C90=N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead. BRKT
AUM02370100003 CLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP, OWC

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order