



CLIFE-PRO-SQ

Lifelight Pro Square Emergency, Recessed Mount,
CLP, Clevertest Plus



PRODUCT INFORMATION	
Part Number	CLIFE-PRO-SQ
MIC	UKT00000006501
Description	Lifelight Pro Square Emergency, Recessed Mount, CLP, Clevertest Plus
Material	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (98mm with adaptor plate)
Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x White LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	398lm (Emergency)
Power Factor	0.366
Supply Current	0.054A
Power Consumption	0.4Watts (Standby), 2.7 Watts (Max)
Inrush Current (Peak/Duration)	12.1A/87µs
Earth Leakage	0.357mA
Operating Temperature	0°C to 40°C
IP Rating	IP20
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Emergency Duration	180 Minutes
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598-2-22, BS 5266
Compliance Marking	UK CE



CLIFE-PRO-SQ

Lifelight Pro Square Emergency, Recessed Mount,
CLP, Clevertest Plus

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
3730045	Battery
1100851	LED Panel
UKM02370070002	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order