

CLEVERTRONICS CLP LIFELIGHT PRO



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO
MIC	UKT02310030001
Description	CLP Premium LifeLight PRO, High Performance, Recessed Emergency Light with Clevertest Plus Enabled
Construction	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Total lumen output	350lm (Emergency)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts 			
Luminaire Classification	X	0	AD	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550229	BATT:LP 3.2V 6400mAh 200mm lead, Sleeve
1100839	Lifelight Pro UK Head Assbly,Rnd,Large+Ring, Gen 2
UKM02370070001	LifelightPro, Control Only, 475mA, LP, OWC

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.