



CLIFE-PRO

Lifelight Pro Emergency, Recessed Mount, CLP, Clevertest Plus



PRODUCT INFORMATION	
Part Number	CLIFE-PRO
MIC	UKT02310030002
Description	Lifelight Pro Emergency, Recessed Mount, CLP, Clevertest Plus
Material	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x White LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V AC; 50Hz
Supply Current	31mA
Power Consumption	0.4Watts (Standby), 2.7 Watts (Max)
Operating Temperature	0°C to 40°C
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Inrush Current (peak/duration)	12.1A/87µs
Earth Leakage	0.357mA
Total Lumen Output	398lm (Emergency)
IP Rating	IP20
Emergency Duration	180 Minutes
Compliance Marking	UK CA CE
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598-2-22, BS 5266



CLIFE-PRO

Lifelight Pro Emergency, Recessed Mount, CLP,
Clevertest Plus

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553229	Battery
1100897	LED Assembly
UKM02370070002 CLIFE-PRO-CKIT-475	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order