



## CLIFE-RECSP-HV-BLK

CLEVERTRONICS LP LIFELIGHT RECESSED EMERGENCY  
WITH IP44 SPLASH PROOF HEAD, BLACK



### PRODUCT INFORMATION

Part Number	CLIFE-RECSP-HV-BLK
MIC	AUD02820090001
Description	LP Premium Lifelight, Recessed Emergency Light with IP44 Splash Proof Head, Black
Construction	PC/ABS head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 51mm x 42mm (Control pack) 95mm Head diameter
Ceiling Hole Cut-Out	85mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
IP Rating	IP44 (parts below ceiling) IP20 (parts above ceiling), see image below
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	Battery
1100762	Emergency LED Head Assembly
AUM02870080001 CLIFE-CKIT-HV	Emergency Driver Pack
8003191	Emergency Node – HIVE (RF)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

IP Ratings:

