

CLIFE-RECSP-HVG CLEVERTRONICS CLP LIFELIGHT RECESSED EMERGENCY WITH IP44 SPLASH PROOF HEAD



PRODUCT INFORMATION		
Part Number	CLIFE-RECSP-HVG	
MIC	UKD02820020001	
Description	CLP Premium Lifelight, High Performance, Recessed Emergency Light with IP44 Splash Proof Head, Supplied with alternate Corridor Lens	
Construction	PC/ABS head	
Dimensions L x W x H	232mm x 51mm x 42mm (Control pack) 95mm Head diameter	
Ceiling Hole Cut-Out	85mm	
Minimum Ceiling Depth	120mm	
Operating Mode	Non-maintained	
Testing System	Zoneworks XT HIVE (RF)	
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), 3.2V 3200mA (with battery sleeve), Clevertronics	
Charging Method	Intelligent current limited constant voltage	
Lamp(s)	1 LED	
Operating Voltage	220-240V AC; 50Hz	
Power Consumption	1.4 Watts (Standby), 4.7 Watts (Max)	
Total lumen output	189lm (Area Lens - fitted), 171lm (Corridor Lens – supplied in box)	

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.





CLIFE-RECSP-HVG CLEVERTRONICS CLP LIFELIGHT RECESSED EMERGENCY WITH IP44 SPLASH PROOF HEAD

PRODUCT INFORMATION			
Rated Emergency Duration	180 minutes		
IP Rating	IP44 (parts below ceiling) IP20 (parts above ceiling), see image below		
Operating temperature	0°C to 40°C		
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts 		
Luminaire Classification	X 0 ADF 180		
Conformity	BS EN 60598-2-22, BS 5266		

IP Ratings: ABOVE CEILING: IP20 //// BELOW CEILING: IP44

REPLACEMENT PARTS		
PART NUMBER	DESCRIPTION	
1550092	BATT:LP 3.2V 3200mAh 260mmLead,NB,Sleeve	
1100764	Lifelight, WP IP44 Head Assembly, Area lens	
UKM02870010001 CLIFE-CKIT-HVG-500	Lifelight, Control Only, 500mA, LP, HVG, OWC (incl. HVG node)	
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna	

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

