





CLIFE-SM-D2

CLEVERTRONICS LP LIFELIGHT SURFACE MOUNT EMERGENCY, DALI-2



PRODUCT INFORMATION

| | |
|--------------------------------|---|
| Part Number | CLIFE-SM-D2 |
| MIC | AUD02210290001 |
| Description | LP Premium Lifelight, High Performance, Surface Mounted Emergency Light, DALI-2 |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Weight | 0.6kg |
| Operating Mode | Non-maintained |
| Testing System | DALI-2 |
| Battery | Lithium Iron Phosphate, 3.2V 3200mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | 1 x High Intensity LED |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1.3W (Standby), 4.5W (Max) |
| Inrush Current (Peak/Duration) | 0.3A/3668μs |
| Earth Leakage | N/A |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =D40 C ₉₀ =D40 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) |  |
| Appliance Class |  Class II double insulated |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1550030 | Battery |
| 8050176 | LED Strip |
| 8002941 | Driver |
| 8003062 | DALI-2 Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.