

CLEVERTRONICS CLP LIFELIGHT SURFACE MOUNT EMERGENCY (DALI)



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Catalogue Number | CLIFE-SM-DALI |
| MIC | UKD02210040002 |
| Description | CLP Premium LifeLight, High Performance, Recessed Emergency Light |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mount |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Weight | 0.7kg |
| Operating Mode | Non-maintained |
| Testing System | DALI Registered |
| Battery Type and Manufacturer | Lithium Iron Phosphate (LiFePO4), Clevertronics |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | 1 x LED |
| Operating Voltage | 220-240V AC; 50Hz |
| Total Lumen Output | 200lm (Emergency) |
| Power Consumption | 1.0 Watts (Standby), 4.2 Watts (Max) |

PRODUCT INFORMATION

| | | | | |
|-------------------------------|--|---|-----|-----|
| Rated Emergency Duration | 180 minutes | | | |
| IP Rating | IP20 | | | |
| Maximum Case Temperature (TC) | 50°C (no heatsink required for lamp controlgear) | | | |
| Operating temperature | 0°C to 40°C | | | |
| Protection | <ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts | | | |
| Luminaire Classification | X | 0 | ADF | 180 |
| Conformity | BS EN 60598.2.22, BS 5266 | | | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|--|
| 1550030 | BATT:LP 3.2V 3200mAh 260mm lead,noBRKT. |
| 8002942 | PCA: CLIFE CT10260-L5 1C500 UK CTP Vert Connectors |
| 8003060 | PCA: DALI Node #CT10629-Ax |

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.