

## CLEVERTRONICS CLP LIFELIGHT SURFACE MOUNT EMERGENCY (ZONWORKS HIVE)



### PRODUCT INFORMATION

Catalogue Number	CLIFE-SM-HVG
MIC	UKD02810010002
Description	CLP Premium LifeLight, High Performance, Recessed Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	200lm (Emergency)
Power Consumption	1.0 Watts (Standby), 4.2 Watts (Max)

## PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts</li> </ul>			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598.2.22, BS 5266			

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8002942	PCA: CLIFE CT10260-L5 1C500 UK CTP Vert Connectors
8003240	PCA: UK RF Node CT10720-A1 Int Antenna

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.