



## CLIFE-SM-HVG

Lifelight Emergency, Surface Mount, CLP,  
Zoneworks XT Hive



PRODUCT INFORMATION	
Part Number	CLIFE-SM-HVG
MIC	UKD02810010003
Description	Lifelight Emergency, Surface Mount, CLP, Zoneworks XT Hive
Material	PC/ABS head
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	220-240V AC; 50Hz
Supply Current	26mA
Power Consumption	1.3W (Standby), 4.5W (Max)
Inrush Current (Peak/Duration)	0.3A / 3668µs
Earth Leakage	N/A
Operating Temperature	0°C to 40°C
Maximum Case Temperature	50°C
Total Lumen Output	200lm (Emergency)
IP Rating	IP20
Emergency Duration	180 Minutes
Compliance Marking	
Luminaire Classification	X   0   ADF   180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1553030	Battery
8050176	LED Assembly
8003828	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order