

## **CLIFE-SM-WP-DALI-BLK**

## CLEVERTRONICS LP LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY



| PRODUCT INFORMATION      |  |
|--------------------------|--|
| Part Number              | CLIFE-SM-WP-DALI-BLK   |
| MIC                      | AUD02210270002   |
| Description              | LP Premium Lifelight, Weatherproof, Surface Mounted Emergency Light, Black |
| Construction             | Polycarbonate Enclosure  |
| Mounting                 | Surface Mounted  |
| Dimensions L x W x H     | 247mm x 129mm x 51mm   |
| Weight                   | 0.8kg  |
| Operating Mode           | Non-maintained   |
| Testing System           | DALI Registered  |
| Battery                  | Lithium Iron Phosphate, 3.2V 3200mAh                                       |
| Charging Method          | Intelligent Current Limited Constant Voltage                               |
| Lamp(s)                  | 1 x High intensity LED   |
| Operating Voltage        | 240V AC; 50Hz  |
| Power Consumption        | 1.3W (Standby) 4.5W (Max)  |
| IP Rating                | IP65   |
| IK Rating                | IK08   |
| Operating Temperature    | 0°C to 40°C  |
| AS2293 Classification    | C0=D50 C90=D50   |
| Applicable Standards     | AS/NZS3820, CISPR15, AS/NZS2293.3  |
| Compliance Marking (RCM) | <u>&amp;</u>   |

| REPLACEMENT PARTS |             |
|-------------------|-------------|
| PART NUMBER       | DESCRIPTION |
| 1550030           | Battery     |
| 8002941           | Driver      |
| 8050174           | LED Strip   |
| 8003060           | DALI Node   |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

