



CLIFE-SM-WP-DALI-BLK

Lifelight Weatherproof Emergency, Surface Mount, LP, DALI
Emergency, Black



PRODUCT INFORMATION						
Part Number	CLIFE-SM-WP-DALI-BLK					
MIC	UKT00000003301					
Description	Lifelight Weatherproof Emergency, Surface Mount, LP, DALI Emergency, Black					
Construction	Polycarbonate Enclosure					
Mounting	Surface Mounted					
Dimensions L x W x H	247mm x 129mm x 51mm					
Weight	0.8kg					
Operating Mode	Non-maintained					
Testing System	DALI Registered					
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics					
Charging Method	Intelligent Current Limited Constant Voltage					
Lamp(s)	1 x LED					
Operating Voltage	220-240V AC; 50Hz					
Total Lumen Output	200lm (Emergency)					
Power Consumption	1.3W (Standby) 4.5W (Max)					
Rated Emergency Duration	180 minutes					
IP Rating	IP65					
IK Rating	IK08					
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)					
Operating temperature	0°C to 40°C					
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts					
Luminaire Classification	<table border="1"><tr><td>•</td><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	•	X	0	ADF	180
•	X	0	ADF	180		
Conformity	BS EN 60598.2.22, BS 5266					

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550030	Battery
8050174	Lifelight Head
8002918	LED Driver
8003060	LED PCA

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order