

CLIFE-SM-WP-DALI

CLEVERTRONICS CLP LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY



| Part Number | CLIFE-SM-WP-DALI | | | | |
|----------------------------------|--|---|-----|-----|--|
| MIC | UKD02220010002 | | | | |
| Description | CLP Premium Lifelight, High Performance, Weatherproof, Surface Mounted Emergency Light | | | | |
| Construction | Polycarbonate Enclosure | | | | |
| Mounting | Surface Mounted | | | | |
| Dimensions L x W x H | 247mm x 129mm x 51mm | | | | |
| Weight | 0.8kg | | | | |
| Operating Mode | Non-maintained | | | | |
| Testing System | DALI Registered | | | | |
| Battery Type & Manufacturer | Lithium Iron Phosphate (LiFePO4), Clevertronics | | | | |
| Charging Method | Intelligent Current Limited Constant Voltage | | | | |
| Lamp(s) | 1 x LED | | | | |
| Operating Voltage | 220-240V AC; 50Hz | | | | |
| Total Lumen Output | 200lm (Emergency) | | | | |
| Power Consumption | 1.3W (Standby) 4.5W (Max) | | | | |
| Rated Emergency Duration | 180 minutes | | | | |
| IP Rating | IP65 | | | | |
| IK Rating | IK08 | | | | |
| Maximum Case Temperature (TC) | 50°C (no heatsink required for lamp controlgear) | | | | |
| Operating temperature | 0°C to 40°C | | | | |
| Protection | Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts | | | | |
| Luminaire Classification | Х | 0 | ADF | 180 | |
| Conformity | BS EN 60598.2.22, BS 5266 | | | | |

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





CLIFE-SM-WP-DALI

CLEVERTRONICS CLP LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY

| REPLACEMENT PARTS | | | |
|-------------------|---|--|--|
| PART NUMBER | DESCRIPTION | | |
| 1550030 | BATT:LP 3.2V 3200mAh 260mm lead,noBRKT. | | |
| 8050174 | HWSUB: CT10694-D1 (Lifelight Head) | | |
| 8002918 | PCA: CLIFE CT10260-L5 1C500 HIVE Vert Conn (Driver) | | |
| 8003060 | PCA: New DALI #CT10629-Ax | | |

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

