



## CLIFE-SM-WP-HVG-BLK

Lifelight IP65 Weatherproof Emergency, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, Black



### PRODUCT INFORMATION

Part Number	CLIFE-SM-WP-HVG-BLK
MIC	AUD02920040001
Description	Lifelight IP65 Weatherproof Emergency, Surface Mount, LP, Zoneworks XT Hive 2.4GHz, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3W (Standby) 4.5W (Max)
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8050174	LED: PCA: HWSUB: CT10694-D1
8002941	Driver:PCA: CLIFE CT10260-L5 1C650 HV Vert Connectors (incl Hive node)
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order