



CLIFE-SM-WP-HVG

Lifelight IP65 Weatherproof Emergency, Surface Mount, CLP, Zoneworks Hive



PRODUCT INFORMATION

Part Number	CLIFE-SM-WP-HVG				
MIC	UKD02820010002				
Description	Lifelight IP65 Weatherproof Emergency, Surface Mount, CLP, Zoneworks Hive				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	247mm x 129mm x 51mm				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	Zoneworks HIVE (RF) 2.4GHz				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	1 x LED				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	200lm (Emergency)				
Power Consumption	1.3W (Standby) 4.5W (Max)				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)				
Operating temperature	0°C to 40°C				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598.2.22, BS 5266				

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553030	Battery
8050174	LED Panel
8003828	Emergency Driver
8003330	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice