

CLIFE-SM-WP

CLEVERTRONICS CLP LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY



Part Number	CLIFE-SM-WP					
MIC	UKD02320010001					
Description	CLP Premium Lifelight, High Performance, Weatherproof, Surface Mounted Emergency Light, Enabled with Clevertest Plus					
Construction	Polycarbonate Enclosure					
Mounting	Surface Mounted					
Dimensions L x W x H	247mm x 129mm x 51mm					
Weight	0.8kg					
Operating Mode	Non-maintained					
Testing System	Clevertest Plus Enabled (Not activated by default)					
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics					
Charging Method	Intelligent Current Limited Constant Voltage					
Lamp(s)	1 x LED					
Operating Voltage	220-240V AC; 50Hz					
Total Lumen Output	200lm (Emergency)					
Power Consumption	1.0W (Standby) 4.2W (Max)					
Rated Emergency Duration	180 minutes					
IP Rating	IP65					
IK Rating	IK08					
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)					
Operating temperature	0°C to 40°C					
Protection	Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts					
Luminaire Classification	Х	0	AD	180		
Conformity	BS EN 60598.2.22, BS 5266					

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





CLIFE-SM-WP

CLEVERTRONICS CLP LIFELIGHT IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY

REPLACEMENT PARTS			
PART NUMBER	DESCRIPTION		
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.		
8050174	HWSUB: CT10694-D1 (Lifelight Head)		
8002942	PCA: CLIFE CT10260-L5 1C500 UK CTP Vert Connectors (Driver)		

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

