



CLIFE-SM

Lifelight Emergency, Surface Mount, CLP,
Clevertest Plus



PRODUCT INFORMATION

Part Number	CLIFE-SM
MIC	UKD02310040002
Description	Lifelight Emergency, Surface Mount, CLP, Clevertest Plus
Material	PC/ABS head
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	220-240V AC; 50Hz
Supply Current	26mA (Standby), 46mA (Max)
Power Consumption	1.0W (Standby), 4.2W (Max)
Operating Temperature	0°C to 40°C
Maximum Case Temperature	50°C
Inrush Current (Max)	0.3A @ 3668µs
Earth Leakage	N/A
Total Lumen Output	200lm (Emergency)
IP Rating	IP20
Emergency Duration	180 Minutes
Compliance Marking	
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553030	Battery
8050176	LED Assembly
8003836	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order