

## CLEVERTRONICS CLP LIFELIGHT



### PRODUCT INFORMATION

Catalogue Number	CLIFE
MIC	UKD02310030003
Description	CLP Premium Lifelight, High Performance, Recessed Emergency Light with Clevertest Plus Enabled
Construction	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Total lumen output	200lm (Emergency)
Power Consumption	1.4 Watts (Standby), 4.7 Watts (Max)

## PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Maximum Case Temperature (TC)	70°C			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts</li> </ul>			
Luminaire Classification	X	0	AD	180
Conformity	BS EN 60598.2.22, BS 5266			

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550092	BATT:LP 3.2V 3200mAh 260mm lead,no BRKT, With SLEEVE
1100923	UK, LifeLight Head Assembly,Ld:1m, Round, LT, 1LED
UKM02370020002	CLIFE-CKIT-500, Lifelight, Control Only, 500mA, CTP, LP OWC

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.