



CLIFE

Lifelight Emergency, Recessed Mount, CLP, Clevertest Plus



PRODUCT INFORMATION	
Part Number	CLIFE
MIC	UKD02310030004
Description	Lifelight Emergency, Recessed Mount, CLP, Clevertest Plus
Material	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) 95mm Head Diameter (145mm with adaptor plate)
Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V AC; 50Hz
Supply Current	36mA (Standby), 46mA (Max)
Power Consumption	1.0 Watts (Standby), 4.7 Watts (Max)
Operating Temperature	0°C to 40°C
Inrush Current (Max)	0.3A / 3668 µs
Earth Leakage	N/A
Total Lumen Output	200lm
IP Rating	IP20
Emergency Duration	180 Minutes
Compliance Marking	UK CA CE
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)
Luminaire Classification	X 0 AD 18 0
Conformity	BS EN 60598-2-22, BS 5266



CLIFE

Lifelight Emergency, Recessed Mount, CLP,
Clevertest Plus

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1553092	Battery
1100923	LED Assembly
UKM02370020003 CLIFE-CKIT-500	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order